

FL7917, FL7915- FINGER LIFT

DESCRIPTION: Self-adhesive tape consists of Polypropylene carrier coated with high grade pressure sensitive Acrylic water based adhesive, includes non-adhesive zone for an easy peeling and reclosing a package .

FEATURES: Solvent free
Printing technology up to 2 colors
UV-resistant
Excellent ageing.
High clarity.

APPLICATION: Excellent performance tape for an easy-to-use resealable closure of a package.

TYPICAL VALUES

Properties	Unit	Values		Test Method
		FL7917	FL7915	
Thickness film total ± 5%	Micron (Mil)	35 (1.41) 55(2.16)	50 (2.0) 70 (2.7)	PSTC- 133
Tensile strength	N/mm ²	150		ASTM D-882
Elongation	%	210		ASTM D-882
Adhesion to steel	N/inch	8.5 ± 2		PSTC- 101
Tape color	Transparent			
Widths*	mm	30, 42		
Lengths*	M	500, 850		
Core width	mm (in)	76 (3)		

* other sizes upon request

Storage and Shelf Life:

One year from date received when stored at 15-30°C (59-86°F). 50% relative humidity. Out of direct sunlight.

Surface Preparation before application:

The surface to which the tape is applied should be clean, dry, and free of grease and oil.

Warranty:

We recommend each user determine the suitability of the products for the intended use.

This information sheet is based on average results and values derived from practical experience and accumulated data. This data is intended only as a source of information and is given in good faith but without guarantee and does not constitute a warranty of performance properties regarding the products. Customers should independently determine the suitability of this material for their specific purpose, prior to use.

